Class 2

Open – SFIG (SCORE Forced Induction Gas)

DEFINITION

Unlimited four-wheel single and two-seat vehicles.

3.5-liter six (6) cylinder engine with forced air induction engines.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is an open class and all components will be considered open unless restricted herein.

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR1 HELMETS
CR2 PROTECTIVE CLOTHING
CR3 EYE PROTECTION and DENTURES
CR4 FIRST AID KIT
CR5 EMERGENCY SIGNALING DEVICES
CR6 HORNS
CR7 REFLECTORS
CR8 FIRE SUPPRESSION EQUIPMENT
CR9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

CR10 SHOCK ABSORBERS and BUMP STOPS
CR11 SECONDARY SUSPENSION
CR12 WHEELS and TIRES
CR13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR14 STEERING
CR15 BRAKES

ELECTRICAL SYSTEM

CR16 IGNITION
CR17 BATTERIES
CR18 LIGHTS
CR19 STARTERS

FUEL SYSTEM

CR20 FUEL
CR21 FUEL TANKS
CR22 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION AND DRIVELINES

CR23 ENGINE and ENGINE DISPLACEMENT

Maximum engine size is 3.5-liter. Must not have more than six (6) cylinders. Engine may use forced induction. Turbos/supercharger's are open.

If SCORE International at any time during the racing season determines that any particular brand or make of engine has an advantage, we may equalize that engine either by a reduction in cc's or the use of a restrictor. These changes may be required during the racing season.

CR24 ENGINE REPLACEMENT
CR25 TRANSMISSION

DIFFERENTIALS

CR26 THROTTLES
CR27 EXHAUST
CR28 DRIVE SHAFTS
CR29 FLYWHEEL SHIELDS
CR30 FLUID COOLERS
CR31 AUXILIARY EQUIPMENT

©2016 SCORE International, All Rights Reserved

CR32 SUPERCHARGERS and TURBOCHARGERS
Open

VEHICLE SAFETY EQUIPMENT

CR33 ROLL CAGES
Must use minimum of 1.750 x .120 tubing for roll-cage structure.
CR34 SAFETY HARNESS
CR35 SAFETY NETS
CR36 SEATING

GENERAL VEHICLE COMPONENTS

CR37 DRIVERS COMPARTMENT
CR38 DOORS AND LATCHES
CR39 FIREWALLS
CR40 BALLAST
CR41 WEIGHT
Minimum weight of 2,000 pounds.
CR42 FLOORBOARDS
CR43 BUMPERS AND HAZARDOUS PROTRUSIONS
CR44 MIRRORS
CR45 SKID PLATES
CR46 STORAGE
CR47 FENDERS
CR48 CHASSIS and BODY
CR49 HOSES
CR50 IDENTIFICATION MARKINGS
All vehicles in this class are required to run a “sun visor”. This visor must be located in the front windshield opening. This visor must be a minimum of five (5) inches wide from the top of the windshield opening and extend from A-pillar to A-pillar.
SCORE International will use this visor area in its entirety for its advertising purposes.
CR51 ADVERTISING ON VEHICLES
CR52 RADIO EQUIPMENT
CR53 WORKMANSHIP
CR54 TRACKING DEVICE

©2016 SCORE International, All Rights Reserved