Pro Quad

Four-wheel ATV's

DEFINITION

Four-wheel ATV's with motorcycle type engines.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is an open class and all components will be considered open unless restricted herein.

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR1 HELMETS
CR2 PROTECTIVE CLOTHING
CR3 EYE PROTECTION and DENTURES
CR4 FIRST AID KIT
CR5 EMERGENCY SIGNALING DEVICES
CR6 HORNS
CR7 REFLECTORS
CR8 FIRE SUPPRESSION EQUIPMENT
CR9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

CR10 SHOCK ABSORBERS and BUMP STOPS
CR11 SECONDARY SUSPENSION
CR12 WHEELS and TIRES
No motorcycle type tires and wheels. Maximum wheel size is 13".
CR13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR14 STEERING
Minimum shaft diameter is 0.750".
CR15 BRAKES

ELECTRICAL SYSTEM

CR16 IGNITION
CR17 BATTERIES
CR18 LIGHTS
CR19 STARTERS

FUEL SYSTEM

CR20 FUEL
CR21 FUEL TANKS
CR22 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION AND DRIVELINES

CR23 ENGINE and ENGINE DISPLACEMENT
Must use motorcycle-type engine. No automotive engines are allowed.
CR24 ENGINE REPLACEMENT
CR25 TRANSMISSION

DIFFERENTIALS

CR26 THROTTLES
CR27 EXHAUST
CR28 DRIVE SHAFTS
CR29 FLYWHEEL SHIELDS
CR30 FLUID COOLERS
CR31 AUXILIARY EQUIPMENT
CR32 SUPERCHARGERS and TURBOCHARGERS

VEHICLE SAFETY EQUIPMENT

CR33 ROLL CAGES

©2016 SCORE International, All Rights Reserved

CR34 SAFETY HARNESS

Pro Quad - *continued*

CR35 SAFETY NETS

CR36 SEATING

GENERAL VEHICLE COMPONENTS

CR37 DRIVERS COMPARTMENT

CR38 DOORS AND LATCHES

CR39 FIREWALLS

CR40 BALLAST

CR41 WEIGHT

CR42 FLOORBOARDS

CR43 BUMPERS AND HAZARDOUS PROTRUSIONS

CR44 MIRRORS

CR45 SKID PLATES

CR46 STORAGE

CR47 FENDERS

CR48 CHASSIS and BODY

Maximum wheelbase is 52” as measured from center of front axle to center of rear axle at ride height.
Maximum track width is 50” as measured from outside of tire to outside of tire.

CR49 HOSES

CR50 IDENTIFICATION MARKINGS

CR51 ADVERTISING ON VEHICLES

CR52 RADIO EQUIPMENT

CR53 WORKMANSHIP

CR54 TRACKING DEVICE

©2016 SCORE International, All Rights Reserved