Pro UTV

DEFINITION

Four-wheel, two-seat naturally aspirated UTV vehicles

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is a stock production class and all components must remain stock except for those modifications allowed herein.

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR1 HELMETS
CR2 PROTECTIVE CLOTHING
CR3 EYE PROTECTION and DENTURES
CR4 FIRST AID KIT
CR5 EMERGENCY SIGNALING DEVICES
CR6 HORNS
CR7 REFLECTORS
CR8 FIRE SUPPRESSION EQUIPMENT
CR9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

Vehicle must retain stock pivot points. Pivot points may be reinforced. Maximum track width is seventy-seven inches (77").

CR10 SHOCK ABSORBERS and BUMP STOPS

One (1) shock per wheel any location.

CR11 SECONDARY SUSPENSION

No secondary suspension allowed.

CR12 WHEELS and TIRES

Any manufacture tire and wheels

Thirty-three inch (33") maximum tire diameter at 18 lbs. of air pressure

CR13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR14 STEERING

No center steering allowed.

CR15 BRAKES

ELECTRICAL SYSTEM

CR16 IGNITION
CR17 BATTERIES
CR18 LIGHTS
CR19 STARTERS

FUEL SYSTEM

CR20 FUEL
CR21 FUEL TANKS

Fuel cells are mandatory in all SCORE four-wheel class.

CR22 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION AND DRIVELINES

CR23 ENGINE and ENGINE DISPLACEMENT

Must use stock "naturally aspirated OEM engine". Engine must remain in stock location. Maximum engine size is 1000cc.

CR24 ENGINE REPLACEMENT
CR25 TRANSMISSION

Must use stock OEM transmission in stock location

CR26 THROTTLES
CR27 EXHAUST

Open

©2016 SCORE International, All Rights Reserved

Pro UTV *- continued*

ENGINE, TRANSMISSION AND DRIVELINES *- continued*

CR28 DRIVE SHAFTS
Open
CR29 FLYWHEEL SHIELDS
CR30 FLUID COOLERS
Open
CR31 AUXILIARY EQUIPMENT
CR32 SUPERCHARGERS and TURBOCHARGERS

VEHICLE SAFETY EQUIPMENT

CR33 ROLL CAGES
CR34 SAFETY HARNESS
CR35 SAFETY NETS
CR36 SEATING
Must use any manufacture racing seats. No stock seats allowed.

GENERAL VEHICLE COMPONENTS

CR37 DRIVERS COMPARTMENT
CR38 DOORS AND LATCHES
CR39 FIREWALLS
CR40 BALLAST
CR41 WEIGHT
Vehicle must weigh 3000 lbs. (wet) minimum.
CR42 FLOORBOARDS
CR43 BUMPERS AND HAZARDOUS PROTRUSIONS
CR44 MIRRORS
CR45 SKID PLATES
CR46 STORAGE
CR47 FENDERS
CR48 CHASSIS and BODY
Must retain stock frame with stock pivot points. Must retain stock UTV appearance
CR49 HOSES
CR50 IDENTIFICATION MARKINGS
CR51 ADVERTISING ON VEHICLES
CR52 RADIO EQUIPMENT
CR53 WORKMANSHIP
CR54 TRACKING DEVICE

©2016 SCORE International, All Rights Reserved