Pro Quad

Competition Numbers 1A - 49A

Four-wheel ATV's

DEFINITION

Four-wheel ATV's with motorcycle type engines.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is an open class and all components will be considered open unless restricted herein.

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR 1 HELMETS
CR 2 PROTECTIVE CLOTHING
CR 3 EYE PROTECTION and DENTURES
CR 4 FIRST AID KIT
CR 5 EMERGENCY SIGNALING DEVICES
CR 6 HORNS
CR 7 REFLECTORS
CR 8 FIRE SUPPRESSION EQUIPMENT
CR 9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

CR 10 SHOCK ABSORBERS and BUMP STOPS
CR 11 SECONDARY SUSPENSION
CR 12 WHEELS and TIRES

No motorcycle type tires and wheels. Maximum wheel size is 13".

CR 13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR 14 STEERING

Minimum shaft diameter is 0.750".

CR 15 BRAKES

ELECTRICAL SYSTEM

CR 16 IGNITION
CR 17 BATTERIES
CR 18 LIGHTS
CR 19 STARTERS

FUEL SYSTEM

CR 20 FUEL
CR 21 FUEL TANKS
CR 22 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION AND DRIVELINES

CR 3 ENGINE and ENGINE DISPLACEMENT

Must use motorcycle-type engine. No automotive engines are allowed.

CR 24 ENGINE REPLACEMENT
CR 25 TRANSMISSION

©2017 SCORE International, All Rights Reserved

DIFFERENTIALS

CR 26 THROTTLES
CR 27 EXHAUST
CR 28 DRIVE SHAFTS
CR 29 FLYWHEEL SHIELDS
CR 30 FLUID COOLERS
CR 31 AUXILIARY EQUIPMENT
CR 32 SUPERCHARGERS and TURBOCHARGERS

VEHICLE SAFETY EQUIPMENT

CR 33 ROLL CAGES
CR 34 SAFETY HARNESS
CR 35 SAFETY NETS
CR 36 SEATING

GENERAL VEHICLE COMPONENTS

CR 37 DRIVERS COMPARTMENT
CR 38 DOORS AND LATCHES
CR 39 FIREWALLS
CR 40 BALLAST
CR 41 WEIGHT
CR 42 FLOORBOARDS
CR 43 BUMPERS AND HAZARDOUS PROTRUSIONS
CR 44 MIRRORS
CR 45 SKID PLATES
CR 46 STORAGE
CR 47 FENDERS
CR 48 CHASSIS and BODY
Maximum wheelbase is 52” as measured from center of front axle to center of rear axle at ride height.
Maximum track width is 50” as measured from outside of tire to outside of tire.
CR 49 HOSES
CR 50 IDENTIFICATION MARKINGS
CR 51 ADVERTISING ON VEHICLES
CR 52 RADIO EQUIPMENT
CR 53 WORKMANSHIP
CR 54 TRACKING DEVICE

©2017 SCORE International, All Rights Reserved