SCORE Lites

OPEN WHEEL – AIR COOLED

Competition Numbers 1200-1299

DEFINITION

Single or two-seat vehicles limited to air-cooled engines.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is an open production class and all components will be considered open unless restricted herein. Vehicles that raced SCORE previously, and do not meet current specifications, can possibly be modified and "Grandfathered" into current competition. Contact SCORE Tech Director for information.

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR 1 HELMETS AND HEAD NECK RESTRAINTS
CR 2 PROTECTIVE CLOTHING
CR 3 EYE PROTECTION and DENTURES
CR 4 FIRST AID KIT
CR 5 EMERGENCY SIGNALING DEVICES
CR 6 HORNS
CR 7 REFLECTORS
CR 8 FIRE SUPPRESSION EQUIPMENT
CR 9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

Front Suspension

Front suspension is limited to VW Type 1 configuration.
Suspension must be of the twin beam, trailing arm type.
Beam is open. This includes width and manufacturer.
Trailing arms are open. This includes length and manufacturer.
Spindles are open.

CR 10 SHOCK ABSORBERS and BUMP STOPS
CR 11 SECONDARY SUSPENSION
CR 12 WHEELS and TIRES
CR 13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR 14 STEERING
CR 15 BRAKES

ELECTRICAL SYSTEM

CR 16 IGNITION
CR 17 BATTERIES
CR 18 LIGHTS
CR 19 STARTERS

FUEL SYSTEM

CR 20 FUEL
CR 21 FUEL TANKS
CR 22 FUEL FILLERS LINES, VENTS, and CAPS

© SCORE International, All Rights Reserved

SCORE Lites

ENGINE, TRANSMISSION AND DRIVELINES

CR 23 ENGINE and ENGINE DISPLACEMENT

Engine must be VW Type 1 and conform to the following:

It retains a maximum of two (2) valves per cylinder.

Single-seat vehicles do not displace more than 1776cc.

Two-seat vehicles may use a maximum of 1835cc air-cooled engine only with a single carburettor.

All vehicles limited to one (1) carburettor.

CR 24 ENGINE REPLACEMENT

CR 25 TRANSMISSION - Open

CR 26 THROTTLES

CR 27 EXHAUST

CR 28 DRIVE SHAFTS

CR 29 FLYWHEEL SHIELDS

CR 30 FLUID COOLERS

CR 31 AUXILIARY EQUIPMENT

CR 32 SUPERCHARGERS and TURBOCHARGERS

VEHICLE SAFETY EQUIPMENT

CR 33 ROLL CAGES

CR 34 SAFETY HARNESS

CR 35 SAFETY NETS

CR 36 SEATING

GENERAL VEHICLE COMPONENTS

CR 37 DRIVERS COMPARTMENT

CR 38 DOORS AND LATCHES

CR 39 FIREWALLS

CR 40 BALLAST

CR 41 WEIGHT

Minimum 1500 pounds.

CR 42 FLOORBOARDS

CR 43 BUMPERS AND HAZARDOUS PROTRUSIONS

CR 44 MIRRORS

CR 45 SKID PLATES

CR 46 STORAGE

CR 48 CHASSIS and BODY

CR 49 HOSES

CR 50 IDENTIFICATION MARKINGS

CR 51 ADVERTISING ON VEHICLES

CR 52 RADIO EQUIPMENT

CR 53 WORKMANSHIP

CR 54 TRACKING DEVICE

© SCORE International, All Rights Reserved