Pro Quad Ironman

Competition Numbers 75A - 99A

DEFINITION

Four-wheel quad vehicles with motorcycle type engines.

Quad vehicle operated by a single participant for the entire race.

Class competes for individual event class specific trophies and payout

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

COMPETITION REGULATIONS

This class is an open class and all components will be considered open unless restricted herein.

To view these complete sections, click on the following links

General Regulations - http://score-international.com/raceinfo/rule-book/general-regulations-2/

Competition Regulations - http://score-international.com/raceinfo/rule-book/competition-regulations/

Click back button or tab between windows to return to this page

NOTE: *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

SAFETY EQUIPMENT

CR 1 HELMETS
CR 2 PROTECTIVE CLOTHING
CR 3 EYE PROTECTION and DENTURES
CR 4 FIRST AID KIT
CR 5 EMERGENCY SIGNALING DEVICES
CR 6 HORNS
CR 7 REFLECTORS
CR 8 FIRE SUPPRESSION EQUIPMENT
CR 9 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

CR 10 SHOCK ABSORBERS and BUMP STOPS
CR 11 SECONDARY SUSPENSION
CR 12 WHEELS and TIRES

No motorcycle type tires and wheels. Maximum wheel size is 13”.

CR 13 FASTENERS

STEERING AND BRAKE COMPONENTS

CR 14 STEERING

Minimum shaft diameter is 0.750”.

CR 15 BRAKES

ELECTRICAL SYSTEM

CR 16 IGNITION
CR 17 BATTERIES
CR 18 LIGHTS - IMPORTANT See pending June 2022 revision in Competition Regulations Section

Taillight is mandatory.

R 19 STARTERS

FUEL SYSTEM

CR 20 FUEL
CR 21 FUEL TANKS
CR 22 FUEL FILLERS LINES, VENTS, and CAPS

© 2022 SCORE International, All Rights Reserved

ENGINE, TRANSMISSION AND DRIVELINES

CR 23 ENGINE and ENGINE DISPLACEMENT

Engine size is open.

Must use motorcycle-type engine. No automotive engines are allowed.

CR 24 ENGINE REPLACEMENT

CR 25 TRANSMISSION

DIFFERENTIALS

CR 26 THROTTLES

CR 27 EXHAUST

CR 28 DRIVE SHAFTS

CR 29 FLYWHEEL SHIELDS

CR 30 FLUID COOLERS

CR 31 AUXILIARY EQUIPMENT

CR 32 FORCED INDUCTION

VEHICLE SAFETY EQUIPMENT

CR 33 ROLL CAGES

CR 34 SAFETY HARNESS

CR 35 SAFETY NETS

CR 36 SEATING

GENERAL VEHICLE COMPONENTS

CR 37 DRIVERS COMPARTMENT

CR 38 DOORS AND LATCHES

CR 39 FIREWALLS

CR 40 BALLAST

CR 41 WEIGHT

CR 42 FLOORBOARDS

CR 43 BUMPERS AND HAZARDOUS PROTRUSIONS

CR 44 MIRRORS

CR 45 SKID PLATES

CR 46 STORAGE

CR 47 FENDERS

CR 48 CHASSIS and BODY

Maximum wheelbase is 52” as measured from center of front axle to center of rear axle at ride height.
Maximum track width is 50” as measured from outside of tire to outside of tire.

CR 49 HOSES

CR 50 IDENTIFICATION MARKINGS - Refer to CR 50 for special quad specifications

CR 51 ADVERTISING ON VEHICLES

CR 52 RADIO EQUIPMENT

CR 53 WORKMANSHIP

CR 54 TRACKING DEVICE

© 2022 SCORE International, All Rights Reserved