# Sportsman UTV Open/Stock

***Forced Induction and Naturally Aspirated***

**Class Number Range 1800-1819**

Combined open class of forced induction and normally aspirated vehicles.
UTVs produced in quantities of at least 1000 units for sale to the general public.
Vehicles must be production based with additional required safety equipment.
Maximum two persons per vehicle. Only exception is factory designed single-seat UTVs.
Reduced entry fee - No Payout - Class competes for trophies only.

## GENERAL REGULATIONS

**► It is the Entrants responsibility to read and thoroughly understand the complete GENERAL REGULATIONS and COMPETITION REGULATIONS sections in the SCORE Rule Book on our website. Entrants in this class shall comply with all applicable General and Competition Regulations.**

## COMPETITION REGULATIONS

*To view these complete sections, click on the following links*

**General Regulations** - http://score-international.com/raceinfo/rule-book/general-regulations-2/

**Competition Regulations** - http://score-international.com/raceinfo/rule-book/competition-regulations/

*Click back button or tab between windows to return to this page*

***NOTE:*** *The CR abbreviations listed under this class (i.e.CR1 HELMETS) refer to cross reference listings in the Competition Regulation section on this website. These cross-referenced listings are part of the class rules. Where a conflict occurs between the cross- referenced listing and a rule contained under this class, the rule contained under this class has precedence.*

## SAFETY EQUIPMENT

**CR1 HELMETS AND HEAD AND NECK RESTRAINTS**
**CR 2 PROTECTIVE CLOTHING**
**CR3 EYE PROTECTION and DENTURES**
**CR4 FIRST AID KIT**
**CR5 EMERGENCY SIGNALING DEVICES**
**CR6 HORNS**
**CR7 REFLECTORS**
**CR8 FIRE SUPPRESSION EQUIPMENT**
**CR9 SURVIVAL SUPPLIES**

## SUSPENSION COMPONENTS

Maximum track width is seventy-seven inches (77”).

**CR10 SHOCK ABSORBERS and BUMP STOPS**

Must mount in original factory locations.

**CR11 SECONDARY SUSPENSION –** Allowed but all aftermarket suspension components must mount in original factory component mount locations.

**CR12 WHEELS and TIRES**

Any tire and wheel manufacture allowed.
Thirty-three inch (33”) maximum tire diameter at 18 lbs. air pressure.

**CR13 FASTENERS**

## STEERING AND BRAKE COMPONENTS

**CR 14 STEERING** - Center steering is allowed only if vehicle is configured for a single participant.

**CR15 BRAKES**

## ELECTRICAL SYSTEM

**CR16 IGNITION**
**CR17 BATTERIES**
**CR18 LIGHTS -** Sportsman class must run blue light in addition to amber light per **CR 18**
**CR19 STARTERS**

## FUEL SYSTEM

**CR20 FUEL**
**CR 21 FUEL TANK – Stock fuel tank is allowed.** Fuel cell is very highly recommended.


© 2023 SCORE International, All Rights Reserved

# Sportsman UTV Open/Stock

**CR22 FUEL FILLERS LINES, VENTS, and CAPS**

**CR23 ENGINE and ENGINE DISPLACEMENT**

Any UTV type engine is allowed. Maximum engine size is 1000cc.

**CR24 ENGINE REPLACEMENT**

**CR25 TRANSMISSION**

Restricted to a UTV-type transmission

**DIFFERENTIALS**

**CR26 THROTTLES**

**CR27 EXHAUST -** Open

**CR28 DRIVE SHAFTS**

**CR29 FLYWHEEL SHIELDS**

**CR30 FLUID COOLERS -** Open

**CR31 AUXILIARY EQUIPMENT**

**CR32 FORCED INDUCTION – Factory stock turbochargers are allowed.**

**VEHICLE SAFETY EQUIPMENT**

**CR33 ROLL CAGES**

**CR34 SAFETY HARNESS**

**CR35 SAFETY NETS**

**CR 36 SEATING -** Must have driver/co-driver seats designed for racing**.** Any manufacturers racing seat acceptable. Adjustable racing seats must be mounted to seat frames with double locking mechanisms.

**GENERAL VEHICLE COMPONENTS**

**CR 37 DRIVERS COMPARTMENT**

**CR 38 DOORS AND LATCHES -** Must have full coverage side panels or doors with secondary latching device. Area below doors must also be covered. Must have welded or bolted intrusion bar at door area.

**CR 39 FIREWALLS**

**CR 40 BALLAST**

**CR41 WEIGHT**

**CR 42 FLOORBOARDS -** OEM floorboard acceptable when metal skidplate is added.

**CR 43 BUMPERS AND HAZARDOUS PROTRUSIONS -** Aftermarket or custom fabricated front bumper (nerf bar) must be added to all UTV vehicles in this class. Bumper must have a minimum width of 21 inches (54 cm.)

**CR48 CHASSIS and BODY**

**CR49 HOSES**

**CR50 IDENTIFICATION MARKINGS**

**CR51 ADVERTISING ON VEHICLES**

**CR52 RADIO EQUIPMENT**

**CR53 WORKMANSHIP**

**CR54 TRACKING DEVICE**


© 2023 SCORE International, All Rights Reserved